

Contents

..... **1**

..... **6**

..... **8**

..... **14**

..... **18**

..... **20**

..... **23**

C






)



)



)



■

□

■ 0

□

■ C

□

■ F

7

□

■

!

,

F

□

□

□ □ 0

D

WARNING!

□ □

■ T

□ 0

■ F

☐D

☐

☐

■ 3

☐C

☐




■ 8

☐

■ B

☐C

☐



1

7

6

□

1

□8

□

C

□0

□

C

□

□



1

D



!



E

C

)

Model	Pressure value bar		Flow value L/min		
			Rotary motion		
	min	max	min	recommend	max
ZJ10R/11R/12R/13R/13H	140	160	19	26	38
ZJ22H/25H/27H/33H	140	160	19	38	57
ZJ38H/35R/42H/45R	140	160	38	57	76

3

)

5




5



C

8B ! " ! ' !

)



Install ation level	A		B		C	
	min	max	min	max	min	max
	380	381	15	16	15.2	16.8
	474.5	476	20.5	21.5	18.2	19.8
	595.5	597	24.5	25.5	18.2	19.8

Figure 1


□

)1

□

"□ 2

□



)C

□

"□ A

□8

6;

B0 4 ' F (

□

"□

□

"□ A

□

"□ ;

□

;

□0

□


"□%

□C

C

!

□ □



"□ 2

□

)

! % :

"

! % : □

B

7


C

' □

□

C

)




" 0

" F

8

1

!



Upper hook Stopper Upper crossbeam of the forklift carriage

" ☐ B ☐


" ☐) ☐

2 ☐) ☐

! 7 ☐

C ☐


5 ☐)C ☐



Turn to any point of 45° to adjust the short arm

" 2

□2



3

)

5	0	E
---	---	---

Roll Clamp User Manual

A	2	1
	0	5
7	7	1
	A	5

1



)C



□

□

⚠ C

□

⚠ C

□

□ 0

)

D

;

5

4

B

4

F

B

A

D



C



%0

0



"



5



(5

)

D



F

□:

□

F

"

□

F

"

□

□ 5

□

□ :

□

□! ;

□

□"

□

□ C

)

□

□ C

)

C □

C

C

2

C

□

3

! !)

□ !

2

2

□

2

)0

□ □

2

2

6; B0 4 ' F (

□

! !

C !

)

2

□

C

□7

2

□8

2

!

D

□8

□

C

)F

5

5

□

% B)

8)

" ;

7)

1)

□

% B)

)

;)

□

% 2)

8)

1)

0)

7)

5)

7)

8

% 5)

7)

B)

B)

% B)

8)

0)

8)

7)

0)

7)

% %)

4

)

$$\%0; \quad)$$

C 0 ; 4

C 0 2 □; □C

□

□ C

0 ; 4 C 0 2 □; □

!

□

! 4

Roll Clamp User Manual

□)

0 ; 4 C 0 2 □; □

0 □

! C 0 ; 4 C 0 2 □; □

□

" 0 ; 4 C 0 2 □; □

0 ;

4 C 0 2 □; □